

TWO COMPONENT, AMBIENT CURE HIGH VISCOUS ADHESIVE SYSTEM

Fasto fix is a two component multifunctional fast setting, high strength epoxy adhesive system. This is used for spot bonding of large stone & tiles on vertical surfaces & has high mechanical strength & outstanding resistance to water & chemicals. Fast Fix resin & hardener are to be mixed thoroughly in the recommended mixing ratio to achieve optimum results.

Features & Benefits:

- Fasto Fix has high bond strength on damp surfaces.
- Out-standing resistance to water and chemicals.
- It is fast curing (handling strength within 15-30 minutes).
- Allows plumb level adjustments while the stone is in place.
- Setting of drilling, clamps and cutting of stone is not required.
- It has faster productivity due to rapid curing.
- Reduction in labour cost.

Area Of Application:

- Fasto Fix is used as a spot bonding for marbles & granite on concrete surfaces.
- Repairing material for concrete cracks.
- Anchoring grouts for reinforcing steel.
- Fasto Fix adhesive is used for bedding marble, granite & other stone on walls.
- It used for bonding of fabricated components.

Preparation of Substrates:

- All substrate must be clean & dry prior to application of Fasto Fix adhesive system.
- Clean & grind the area of stone where Fasto Fix is to be used by using mechanical wheel grinder with a diamond wheel blade.
- Surface after treatment must be thoroughly cleaned of all laitance, loose material, oil & grease etc.

Application:

- Part A (resin) & Part B (hardener) thoroughly mix together with separate stirrer to get uniform mix mass.
- Take Fasto Fix part A & B in proportion of 100:50 (by weight) and mix thoroughly

until homogeneous paste with uniform colour achieved with putty knife or margin travel.

- It is apply immediately evenly spread on the back of the tile & stone.
- It is apply minimum five daps, one in each corner & one in center, dap thickness must be maintain 3mm.
- The mixture must be used with in its pot-life.

Technical Details:

Description	thixotropic fine paste
Colour	resin (off-white) & hardener (brilliant white)
Density(gm/cc)	resin & hardener-(1.55-1.65)
Pot life	10-15 minutes
Water absorption(after 24hours)	0.30-0.50

Packaging:

1.5kg (1kg resin + 0.5kg hardener)

Shelf Life:

24 months from the date of manufacturing

DISCLAIMER The product information & application details given by the company & its agents has been provided in good faith & meant to serve only as a general guideline during usage. Users are advised to carry out tests & take trials to ensure on the suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problems, quality of other materials used and the on-site workmanship are factors beyond our control, there are no expressed or implied guarantee / warranty as to the results obtained. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.

Dubond Products (India) Pvt. Ltd.
C-3, 1001, Anushruti Tower, S.G. Highway, Thaltej,
Ahmedabad-380054. Gujarat - INDIA
Ph: 91-79-2685 6815 Fax: 91-79-2685 6816
Email: info@dubond.in Website: www.dubond.in
Customer Care : +91 9377177771



BINDS BETTER ! BEAUTIFY !