



STONE SEAL

STAIN PROOF IMPREGNATOR FOR MARBLE AND GRANITE

Dubond's Stone Seal is a stain proof product for compact natural stones, marbles, granites, agglomerates honed or polished both for interior and for exterior. The product does not leave any film on the surface and keeps the natural permeability and colour of the stone unchanged. It protects floorings, coverings, kitchen tops, vanity tops, tables etc. From dirt, stains of oil, coffee, beverages, markers, paint, etc.

Green Building Rating



Low Emission



Low Ecological Impact



Health Care



Water Based

Areas of Application

Ideal for

- Agglomerates honed or polished
- Both for interior and for exterior
- Compact natural stones
- Granites
- Marbles

Features & Benefits :

- Fluorochemical Technology
- Hydrophobic & Oleo Phobic
- Improves Wear Resistant Of Tiles And Stones.
- Non Yellowing
- Stain Resistance
- Transparent Natural Look
- User Friendly
- UV Resistance

Method of Application :

1. Apply using a brush, roller, cloth, sponge, or sprayer.
2. Buffs dry any excess sealer that does not penetrate within 3 to 5 minutes with an absorbent towel or carpet bonnet.
3. Highly porous surfaces may require a second or third application to give full protection.
4. Wait a minimum of 1 hour between applications.
5. May be opened for foot traffic in 2 hours.
6. Achieves a full cure in 24 hours.

■ Features & Benefits :

- It is stain proof
- It does not leave any film on the surface and keeps the natural permeability and colour of the stone unchanged
- It is a penetrating product therefore it does not increase the resistance of marbles or stones containing carbonate against the acid aggression of wine, vinegar, lemon juice, tomato juice, cleaners, etc.
- Gives a better protection from dirt, stains of oil, coffee, beverages, markers, paint

■ Method of application :

1. Apply on the dry and clean surface a thin even layer of stone seal by means of a brush, lambs wool or low pressure sprayer.
2. Two coats wet on wet are required only on the most absorbing materials.
3. Allow to dry completely.
4. For polished materials, remove the dull patina with steel wool pad (type 00) or with a cloth slightly damp with stone seal. For large surfaces, use a floor machine with red pad or fine steel wool pad (type 00).
5. The surface can be opened to foot traffic 3-6 hours after treatment
6. The treatment must not be wet for the next 24 hours, i.e. until the product has completely hardened.

■ Precautions & Limitations :

- For regular maintenance, clean the surface with neutral cleaner. On polished materials, one coat of maintenance wax can be applied every 2-6 months or as needed.
- In case material is released or spilled, clean up the product, which can be reused. Absorb all residues with sand, sawdust etc.

■ Technical Information :

Appearance	Transparent Liquid
Colour	Transparent
Odor	Acetate Solvent
pH	N/A
Spec. Gravity	(20°C): 0.960 Gr. /Cc
Flashing Point	46°C

■ Coverage :

Approximately 1 liter of Stone seal covers about 15 - 25 M² of floor depending upon the substrate.

■ Packing :

Available in 500 ml, 1 Liter, 5 liter and 20 liters containers.

■ Shelf Life & Storage :

12-24 months in original sealed packing kept in cool and dry place. store in a dry place in the original container.

■ Health & Safety Precautions :

Keep out of reach of children. wear suitable protective clothing, gloves, and eye / face protection. after contact with skin wash immediately with plenty of clean water. in case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice.

DISCLAIMER The product information & application details given by the company & its agents has been provided in good faith & meant to serve only as a general guideline during usage. Users are advised to carry out tests & take trials to ensure on the suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problems, quality of other materials used and the on-site workmanship are factors beyond our control, there are no expressed or implied guarantee / warranty as to the results obtained. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.

Dubond Products (India) Pvt. Ltd.

C-3, 1001, Anushruti Tower, S.G. Highway, Thaltej,

Ahmedabad-380054. Gujarat - INDIA

Ph: 91-79-2685 6815 Fax: 91-79-2685 6816

Email: info@dubond.in Website: www.dubond.in

Customer Care : +91 9377177771



BINDS BETTER ! BEAUTIFY !