

TILE & STONE PRIMER

UNDERCOAT PRIMER & ADHESION PROMOTER

Description

Dubond's Tile & Stone Primer is a water base nano particle aqueous dispersion. It is designed as a barrier to prevent water, alkali and other compounds from reaching the substrate surface and to avoid efflorescence that can cause surface discoloration especially in cement substrates.

I Green Building Rating













Areas of Application

- Stones and porous tiles.
- Interior & exterior
- Wall & floors
- Natural porous stones & tiles
- Concrete surfaces before painting or laying of tiles to prevent efflorescence and providing water
- resistance Upper substrate acts as a adhesion promoter

Features & Benefits:

Water base nano particle aqueous dispersion It is designed as a barrier to prevent water, alkali and other compounds from reaching the substrate surface.

Method of Application :

- 1. Wash the substrate by clean water and allow if to dry apply primer by soft bristle brush and led it to dry 6 to 8 hours.
- 2. The surface area has been primed now apply any another product.

Precaution & limitations :

It's applied as a supplied, do not dilute it.

■ Technical Information :

Appearance Limpid viscous emulsion

Colour White liquid

pH N/A

Spec. Gravity (20°C): 0.820 Gr. /Cc

Flashing Point 38°C



Coverage :

Approximately 1 liter of Stone seal covers about 10 - 15 M² of floor depending upon the substrate.

Packing:

Avaliable in 500 ml, 1 Liter, 5 liter and 20 liters containers.

Shelf Life & Storage :

6 months in original sealed packing kept in cool and dry place. store in a dry place in the original container.

Health & Saftey Precautions :

Keep out of reach of children. wear suitable protective clothing, gloves, and eye / face protection. after contact with skin wash immediately with plenty of clean water. in case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice.



DUBOND PRODUCTS INDIA PVT. LTD.

C-3, 1001, Annushruti Tower, S.G. Highway, Thaltej, Ahmedabad - 380054. GUJARAT - INDIA

Email: info@dubond.in,

OFFICE NO.: +91-79-2685 6815, Web: www.dubond.in,

Customer Care: +91 9377177771

DISCLAIMER The product information & application details given by the company & its agents has been provided in good faith & meant to serve only as a general guideline during usage. Users are advised to carry out tests & take trials to ensure on the suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problems, quality of other materials used and the on-site workmanship are factors beyond our control, there are no expressed or implied guarantee / warranty as to the results obtained. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.