



# PRIME PUTTY



## WHITE CEMENT BASED PUTTY FOR INTERIOR AND EXTERIORS.

Dubond's Prime Putty is a white cement-based fine powder. It serves as filler/ leveller for walls and ceilings. It provides a waterproof surface with excellent smoothness, good adhesion, good breathing properties, and seals porosity for uniform deposition of finished paint and enhances durability. It is a water resistant white cement based putty ideal for use on concrete/mortar walls (internal and external) and ceilings. It fills the fine pores of mortar/concrete walls and ceilings and provides a white, smooth and dry surface, essential for painting. It helps you combine the suave look with beauty for interiors and exteriors.

No need to apply any kind of primer on it before application of paint or distemper. It prevents the growth of algae and fungi on walls. prime putty can be applied even on moist surface (internal/external). It has more adhesive strength, durability and enhances the life of paints. Being white cement based, does not require water curing.

### Green Building Rating



Mineral  $\geq$  30%



Low Emission



Low Ecological Impact



Health Care



Water Based

### Areas of Application

- Walls and ceilings
- ideal for use on concrete/mortar walls (internal and external)
- It can be used any type of surface like concrete, rendered wall, hollow block, precast walls, concrete ceilings, calcium silicate bricks etc.

### Features & Benefits :

- Prime Putty can be applied on both interior and exterior surfaces.
- Prime Putty does not require any curing.
- Prime Putty gives a smooth and glossy finish.
- Any kind of paint or distemper can be applied on it.
- Being a cementitious material it has better adhesiveness and durability.
- It can be applied on used surface after proper preparation.
- It is in dry powder form and does not produce any kind of unpleasant smell at the time of application.
- It is water resistant and can be applied on moist surface.
- It prevents the growth of algae and fungi on walls.
- No need to apply any kind of primer on it before application of paint/distemper.

### Application Procedure

1. Remove all loosely adhering material from the wall surface with the help of emery stone, putty blade or wire brush and clean water. The substrate should be clean, free from dust, grease and loose materials.
2. Dry and absorbent surfaces should be moistened with sufficient quantity of clean water.
3. Mix Prime putty with 30% - 35% clean water slowly to make paste. Continue the mixing for 10-15 minutes till a uniform paste is formed.
4. After thoroughly mixing the Prime Putty apply the first coat on already moistened wall surface from bottom to upward direction uniformly with the help of putty blade. This would ensure less wastage and proper finish.

**DUBOND®**

BONDS BETTER! BEAUTIFY!

5. After drying of first coat of putty just rub the surface gently with wet sponge or rub the surface very gently with the putty blade in order to remove the loose particles.
6. Allow the surface to dry for atleast 3 hours and then apply second coat of putty.
7. Leave the surface to dry completely. After drying of second coat remove marks if any with the help of moist sponge or rub the surface very gently with the putty blade.
8. Leave the surface to dry preferably for overnight. Always prepare a required quantity of putty and use it within 2-3 hrs. of mixing with water The total thickness of the coats should be limited to maximum 1.5mm.
9. It is not essential to rub the surface done with Prime Putty however if you need to remove unevenness before applying any kind of paint/distemper, gently level the walls/ceiling surface with very fine water proof emery paper of not less than 500 number to get a glossy white surface.

**Note**

Generally the cause of efflorescence on the walls surface is the brick masonry, which is due to the quality of bricks, sand and water, If the effect of efflorescence on the brick masonry seems to be very high then proper care should be taken to control the efflorescence by applying Dubond's Hydro Prime Single Coat. The efflorescence problem on brick masonry if exists impairs the bonding of Prime Putty as is with any other product.

**Technical Specification**

Compressive Strength (28 Days)	<b>14.00 N/mm<sup>2</sup></b>
Surface Hardness	<b>3.0</b>
Tensile Adhesion (28 Days)	<b>2.69 N/mm<sup>2</sup></b>
Water Demand	<b>30-35% by volume (depending on weather and site needs)</b>
Pot Life	<b>2 Hours</b>
Maximum Thickness (Two Coat)	<b>1.5mm</b>

**Coverage :**

The coverage area of Prime Putty on smooth normal mortar wall is 20 to 25 Sq.Ft/Kg/mm in double coat. The coverage area, however, will depend upon the quality of the substrate.

**Packing :**

Prime Putty is available in 1Kg, 5Kg, 20Kg. and 40Kg Packs.

**Storage :**

Store in dry moisture free area. Storage Life is 6 months

**Safety :**

Use Gloves. Non Toxic.

**DISCLAIMER** The product information & application details given by the company & its agents has been provided in good faith & meant to serve only as a general guideline during usage. Users are advised to carry out tests & take trials to ensure on the suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problems, quality of other materials used and the on-site workmanship are factors beyond our control, there are no expressed or implied guarantee / warranty as to the results obtained. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products.

**DUBOND PRODUCTS INDIA PVT. LTD.**  
 C-3, 1001, Annushruti Tower, S.G. Highway,  
 Thaltej, Ahmedabad - 380054. GUJARAT - INDIA  
 Email : info@dubond.in,  
 OFFICE NO. : +91-79-2685 6815,  
 Web: www.dubond.in,  
**Customer Care : +91 9377177771**

